

HYDRAULIKKRØR

1905-XX



Produktgruppe	630
Produktinfo	E355N Cr-VI-free
Produkt info2	EN 10305-4
Type	Hydraulikk stål
Materiale	E355+N (st. 52,4)

Artikkelnr.	OD mm	Tykkelse mm	PN MPa	Vekt kg/m
19051420	14	2	41,1	0,59
19051515	15	1.5	25,9	0.50
19051520	15	2.0	38,1	0.64
19051615	16	1,5	24,2	0,55
19051620	16	2.0	35,5	0.69
19051625	16	2,5	47,4	0,83
19051815	18	1.5	21,3	0.61
19051820	18	2.0	31,2	0.79
19052020	20	2.0	27,9	0.88
19052025	20	2,5	37,0	1,08
19052030	20	3,0	46,6	1,25
19052220	22	2.0	25,2	0.99
19052520	25	2,0	22,0	1,13
19052525	25	2,5	29,1	1.39
19052530	25	3,0	36,4	1.63
19052820	28	2.0	19,5	1.28
19052830	28	3,0	32,2	1,85
19053020	30	2.0	18,1	1,38
19053030	30	3,0	29,9	2.00
19053040	30	4,0	42,3	2.57
19053520	35	2.0	15,4	1.63
19053530	35	3,0	25,3	2.37
19053830	38	3,0	23,2	2.37
19053840	38	4,0	32,6	3.35
19053850	38	5,0	42,5	4.07
19054230	42	3,0	20,9	2.89
19054240	42	4,0	29,3	3,75
19125050	50	5,0	31,5	5,55
19126050	60	5,0	25,9	6,78