

RØRKUPLING

5569-86



Produktinfo	Rørkupling i syrefast materiale type Grip E.
Produktgruppe	500
Type	Rørkupling
Materiale	AISI 316
Produkt info2	Pakning: EPDM. Kan også leveres i NBR.
Beskrivelse	Temperatur EPDM: 26,9-168,3 mm: -30C til +125C Over 180 mm: -20C til +80C Temperatur NBR: -20C til +80C

Artikkelnr.	Dimension range	Annen info
55698626S	26,4-27,5	70 Bar
55698628S	27,5-28,5	70 Bar
55698630S	29,5-30,6	70 Bar
55698633S	33,0-34,3	60 Bar
55698635S	34,5-35,6	60 Bar
55698638S	37,5-38,6	60 Bar
55698642S	41,7-43,0	50 Bar
55698644S	44,0-45,1	50 Bar
55698648S	47,6-50,5	50 Bar
55698654S	53,3-54,6	50 Bar
55698657S	56,3-57,7	50 Bar
55698660S	59,5-61,0	40 Bar
55698670S	69,0-71,0	40 Bar
55698673S	72,1-73,8	40 Bar
55698676S	75,2-77,0	35 Bar
55698680S	79,0-80,8	35 Bar
55698684S	83,0-85,0	35 Bar
55698688S	87,0-89,9	35 Bar
556986101S	100,4-102,8	35 Bar
556986104S	102,8-106,1	35 Bar
556986108S	106,8-109,2	35 Bar
556986110S	108,8-111,4	35 Bar
556986114S	113,0-115,5	35 Bar
556986129S	127,6-131,1	32 Bar
556986133S	131,5-134,4	32 Bar
556986139S	138,1-141,6	32 Bar
556986141S	139,6-142,8	32 Bar
556986154S	152,3-156,1	32 Bar
556986159S	157,3-160,7	32 Bar

Artikelnr.	Dimension range	Annen info
556986168S	166,5-170,1	32 Bar
556986193S	192,0-196,0	20 Bar
556986206S	202,0-208,0	20 Bar
556986219S	216,0-221,0	20 Bar
556986225S	222,0-227,0	16 Bar
556986229S	228,0-232,0	16 Bar
556986244S	242,0-247,0	15 Bar
556986254S	250,0-256,0	14 Bar
556986267S	264,0-269,0	13,5 Bar
556986273S	270,0-275,0	13 Bar
556986306S	302,0-308,0	10,5 Bar
556986323S	320,0-327,0	9,5 Bar
556986326S	322,0-329,0	9,5 Bar
556986355S	352,0-359,0	8,5 Bar
556986406S	402,0-410,0	7,0 Bar
556986429S	426,0-431,0	6,5 Bar
556986442S	439,0-444,0	6,5 Bar
556986457S	454,0-459,0	6,0 Bar
556986508S	505,0-510,0	4,0 Bar
556986531S	528,0-534,0	4,0 Bar
556986558S	556,0-562,0	3,5 Bar
556986609S	606,0-613,0	2,0 Bar