

PLASTSPIRAL SVART

5526-00



Produktinfo	Kraftig type
Type	Slangebeskyttelse
Temperatur min. °C	-70
Temperatur maks. °C	+80
Produktgruppe	552

Artikkelnr.	Tykkelse mm	Dimension range	Farge	Lengde
552600016	1,6 mm	11-17 mm	Svart	6 m
552600020	2,0 mm	17-21 mm	Svart	6 m
552600025	2,5 mm	21-27 mm	Svart	6 m
552600032	2,5 mm	27-35 mm	Svart	6 m
552600040	3,0 mm	35-42 mm	Svart	6 m
552600050	3,0 mm	42-58 mm	Svart	6 m
552600075	4,0 mm	58-70 mm	Svart	6 m
552600090	4,5 mm	70-90 mm	Svart	6 m
552600110	5,0 mm	90-115 mm	Svart	6 m
552600140	5,5 mm	115-135 mm	Svart	6 m
552600160	5,5 mm	135-165 mm	Svart	6 m
552625040	3,0 mm	35-42 mm	Svart	25 m
552625050	3,0 mm	42-58 mm	Svart	25 m
552650016	1,6 mm	11-17 mm	Svart	50 m
552650020	2,0 mm	17-21 mm	Svart	50 m
552650025	2,5 mm	21-27 mm	Svart	50 m
552650032	2,5 mm	27-35 mm	Svart	50 m
552610016	1,6 mm	11-17 mm	Svart	1 m
552610020	2,0 mm	17-21 mm	Svart	1 m
552610025	2,5 mm	21-27 mm	Svart	
552610032	2,5 mm	27-35 mm	Svart	1 m
552610040	3,0 mm	35-42 mm	Svart	1 m
552610050	3,0 mm	42-58 mm	Svart	1 m
552610075	4,0 mm	58-70 mm	Svart	1 m
552610090	4,5 mm	70-90 mm	Svart	1 m
552610110	5,0 mm	90-110 mm	Svart	1 m
552600200	165-220 mm	Svart		
552610140	5,5 mm	115-135 mm	Svart	1 m
552610160	5,5 mm	135-165 mm	Svart	1 m