


Blanking ends

VS-R ... -WD

VS-R ... -WD-1.4571

- with hexagon socket
- with soft seal made from NBR* (e.g. Perbunan) for steel
- with soft seal made from FKM (e.g. Viton) for stainless steel (1.4571)
- Inch studs type E to DIN EN ISO 1179-2



J

PN bar (psi)	DIN - ISO 228 (R..., DIN 259)	Model	kg/ 100 pc.	D	l	i	S	O-ring	Blanking ends	Blanking ends
									VS-R ... -WD	Stainless steel (1.4571) VS-R ... -WD-1.4571
									Art. no.	Art. no.
400 (5801)	G 1/8 A	VS-R 1/8 -WD	0.6	14	12	8	5	3 x 1	WAL036856	WAL602800
	G 1/4 A	VS-R 1/4 -WD	1.4	19	17	12	6	5 x 1	WAL036858	WAL374787
	G 3/8 A	VS-R 3/8 -WD	2.1	22	17	12	8	7 x 1	WAL036860	WAL374841
	G 1/2 A	VS-R 1/2 -WD	4.0	27	19	14	10	4.5 x 1.5	WAL036862	WAL372597
	G 3/4 A	VS-R 3/4 -WD	7.5	32	21	16	12	6 x 1.5	WAL036864	WAL602802
	G 1 A	VS-R 1 -WD	11.8	40	22.5	16	17	8.5 x 1.5	WAL036866	WAL374498
250 (3626)	G 1 1/4 A	VS-R 1 1/4 -WD	18.6	50	22.5	16	22	10 x 1.5	WAL036868	WAL371504
	G 1 1/2 A	VS-R 1 1/2 -WD	24.7	55	22.5	16	24	12 x 2	WAL036870	WAL609394
400 (5801)	G 1 1/4 A	VS-R 1 1/4 -WD/PN 400	28.3	50	28	20	22	15 x 2	WAL372905	
	G 1 1/2 A	VS-R 1 1/2 -WD/PN 400	39.2	55	30	22	24	20 x 2	WAL372989	

⚠ Caution: The pressure specifications refer to the steel version. For the stainless steel version (1.4571), please refer to the pressure specifications on page B5.
*For FPM (e.g. Viton) see price list / available on request